




Fire-Rated Steel Door, Wall, & Frame Systems

Rated for 60-120 Minutes | Narrow Profile | Large Panes

forster fuego® light



Slim Steel Framing



Hose-Stream



Positive Pressure



TGIC-Free Powder Color



LEED



Fire-Resistive (ASTM E119 & UL 263)

LISTINGS AND STANDARDS

- ASTM E119
- NFPA 80
- UL 10B
- Intertek SpecID: #68428
- NFPA 252
- UL 10C
- UL 263
- #68901
- UL 1784
- #69916



PRODUCT OVERVIEW

- Fire-rated for 60 to 120 minutes, Intertek-listed
- Listed as a wall assembly in accordance with UL 263 / ASTM E119, and therefore not subject to opening-protective size restrictions
- Available in a stock range of TGIC-free powder-coat colors and finishes, as well as brushed stainless steel (doors only) and custom colors
- Narrow sight lines / profiles
- Utilizes large individual panes of AGC Pyrobel® Fire-Resistive Glazing (ultra-clear, low iron glazing)
- AGC Pyrobel® Vision Line Butt-Glazed install options available with ultra-slim 4 mm joint
- Concealed hardware options available
- Factory-installed McGrory hardware packages available to meet project needs
- Frames supplied as fully fabricated K/D assembly
- Unique factory-installed hardware, including: tubular exit devices, concealed hinges, concealed closers, and electrified options to integrate with access-control systems

TECHNICAL INFORMATION

Makeup	Finishes	Applications	Minute Rating	Door Opening		Other Than Doors		
				Max. Width	Max. Height	Max. Exposed	Max. Width	Max. Height
Steel	• Brushed/Polished Stainless Steel • TGIC-Free Powder-Coat Colors (Stock & Custom)	Doors Borrowed Lites Sidelites Transoms Walls Windows	60 min	48"	121-1/2"	7200 in ²	120"	120"
			90 min	42-13/16"	118-7/16"	n/a	n/a	n/a
			120 min	N/A	N/A	7200 in ²	120"	120"

CALL FOR A QUOTE: 800-220-3749

EMAIL: fire@mcgrory.com

VISIT US AT: mcgroryfire.com



McGRORYGLASS
SYSTEMS



Detail Drawings | 60-Minute-Rated System is Displayed



#69916

