



Fire-Rated Steel Door & Window Frame Systems

Rated for 20-90 Minutes | Narrow-Profile Fire- & Smoke-Rated Options


forster presto



Slim Steel
Framing



S-Label
UL 1784



Hose-Stream



Positive
Pressure



TGIC-Free
Powder Color



Fire-Protective

LISTINGS AND STANDARDS

- NFPA 80
- NFPA 105
- NFPA 252
- NFPA 257
- UL 9
- UL 10B
- UL 10C
- UL 1784
- ULC S104
- ULC S106
- Intertek SpecID:
#68427
#69917



PRODUCT OVERVIEW

- Fire-rated for 20 to 90 minutes, Intertek-listed
- S-label smoke door option available (UL 1784)
- Narrow sight lines / profiles
- Concealed hardware options available
- Frames supplied as fully fabricated K/D assembly
- Factory-installed McGrory hardware packages available to meet project needs
- Available in a stock range of TGIC-free powder-coat colors and finishes, as well as brushed stainless steel and custom colors

TECHNICAL INFORMATION

Makeup	Finishes	Applications	Minute Rating	Door Opening		Other Than Doors		
				Max. Width	Max. Height	Max. Exposed	Max. Width	Max. Height
Steel	• Brushed/Polished Stainless Steel Cladding • TGIC-Free Powder-Coat Colors (Stock & Custom)	Doors Borrowed Lites Sidelites Transoms Walls Windows	20 min	42"	96"	6396 in ²	106- 1/2"	106- 1/2"
			45 min	42"	96"	3855 in ²	95"	95"
			60 min	42"	96"	3855 in ²	95"	95"
			90 min	42"	96"	2627 in ²	84"	84"

CALL FOR A QUOTE: 800-220-3749

EMAIL: fire@mcgrory.com

VISIT US AT: mcgroryfire.com



McGRORYGLASS
SYSTEMS



Fire-Rated Steel Door & Window Frame Systems

Detail Drawings



Intertek SpecID:
#68427
#69917

